

MATERIAL SAFETY DATA SHEET		SPECIAL FIRE FIGHTING PROCEDURES: For fires with this material, do not enter any enclosed or confined fire space without proper protective equipment, including self-contained breathing apparatus, to protect against the effects of hazardous combustion byproducts.	Flush final traces with water. Keep spills and cleaning run-off out of municipal sewers or open bodies of water.
MFG. BY: SAFE ENCASEMENT SYSTEMS			WASTE DISPOSAL METHOD: Disposal should be in accordance with Federal, state and local regulations for water-based coatings. Coagulate the emulsion by the stepwise addition of ferric chloride and lime. Incinerate the solids and contaminated diking material at a permitted facility, according to Federal, State and local regulations.
EMERGENCY CONTACT: (800) 424-9300		SECTION V - REACTIVITY DATA	PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: <i>KEEP FROM FREEZING.</i>
ADDRESS: 7860 Dana Point Court, Suite R, Las Vegas, NV 89117-1927		STABILITY: Stable under normal conditions. CONDITIONS TO AVOID: <i>Keep from freezing.</i> INCOMPATIBILITY (Materials to Avoid): None reasonably foreseeable.	
Revised: January 2000.		Hazardous Polymerization: Will not occur.	
Information Phone: 888/ 277 / 8834		HAZARDOUS DECOMPOSITION OF BYPRODUCTS: Will not occur.	SECTION VIII - CONTROL MEASURES.
SECTION I - PRODUCT ID.		SECTION VI - HEALTH HAZARD DATA	VENTILATION: GENERAL VENTILATION IS RECOMMENDED DURING NORMAL USE. LOCAL VENTILATION MAY BE REQUIRED DURING CERTAIN OPERATIONS TO PREVENT INHALATION OF VAPORS.
PRODUCT NUMBER: SE-150		EFFECTS OF OVEREXPOSURE:	RESPIRATORY PROTECTION: WEAR respirator (MSHA or NIOSH APPROVED or the equivalent) ORGANIC VAPOR/PARTICULATE RESPIRATOR. IN CASE OF POOR VENTILATION or exposure to spray mist, USE NIOSH APPROVED ORGANIC VAPOR MASK.
PRODUCT NAME: 100% Acrylic Sealant.		INHALATION of excessive vapor/mist can cause headache, nausea and irritation of the nose, throat and lungs.	PROTECTIVE GLOVES: IMPERVIOUS GLOVES FOR PROLONGED OR REPEATED CONTACT.
PRODUCT CLASS: Elastomeric 100% Acrylic.		EYE CONTACT: slightly irritating to eyes.	EYE PROTECTION: Chemical Splash Goggles (ANSI 2-87.1) or equal.
SECTION II - HAZARDOUS INGREDIENTS		SKIN EXPOSURE: irritating to skin upon prolonged or repeated contact.	OTHER PROTECTIVE EQUIPMENT AND MEASURES: UNHINDERED ACCESS TO SAFETY SHOWER AND EYE WASH STATIONS. AS A GENERAL HYGIENIC PRACTICE, WASH HANDS AND FACE AFTER USE. Showers and cleaning of clothes are recommended. Use approved clothing when working around ACM or lead-based paints.
None known at a hazardous level. This product contains no heavy metals or fibers.		EMERGENCY AND FIRST AID PROCEDURES: For inhalation, move subject to fresh air. For eye contact, flush with large amounts of water for at least 15 minutes. See a physician if irritation persists. Wash effected skin area with soap and water. If swallowed, dilute by giving 2 glasses of water to drink and CALL A PHYSICIAN IMMEDIATELY. Never give anything by mouth to an unconscious subject.	SECTION IX - REGULATORY INFO.
SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS		OTHER PRECAUTIONS: DO NOT TAKE INTERNALLY. KEEP AWAY FROM CHILDREN.	DOT PROPER SHIPPING NAME: Not Regulated - Follow all applicable OSHA and EPA regulations concerning normal latex spraying activities.
APPEARANCE: Milky White Paste		SECTION IV - FIRE & EXPLOSION HAZARD DATA	
BOILING POINT: Variable		FLAMMABILITY CLASSIFICATION:	
Specific Gravity: Greater than 1.0 (H ₂ O = 1.0)		DOT - NOT REGULATED	
VAPOR DENSITY: less than 1.0		FLASH POINT - N/A	
EVAPORATIVE RATE: equal to water		LEL - N/A	
WEIGHT PER GALLON: 8.6 – 8.9 lb.		EXTINGUISHING MEDIA: N/A	
PERCENT VOLATILE (by volume): 37 to 40%		UNUSUAL FIRE & EXPLOSION HAZARDS: Material can splatter above 212°F Polymer film can burn.	
SECTION IV - FIRE & EXPLOSION HAZARD DATA			
FLAMMABILITY CLASSIFICATION:		SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE.	
DOT - NOT REGULATED		STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Keep Spectators away. WEAR SKIN, EYE, AND RESPIRATORY PROTECTION DURING CLEANUP. Dike and contain with inert absorbent materials (sand, earth, etc.). Transfer collected materials to containers for recovery or disposal.	
FLASH POINT - N/A			
LEL - N/A			
EXTINGUISHING MEDIA: N/A			
UNUSUAL FIRE & EXPLOSION HAZARDS: Material can splatter above 212°F Polymer film can burn.			