

MATERIAL SAFETY DATA SHEET		SPECIAL FIRE FIGHTING PROCEDURES: For fires with this material, do not enter any enclosed or confined fire space without proper protective equipment, including self-contained breathing apparatus, to protect against the effects of hazardous combustion byproducts.	Floors may be slippery, use care to avoid falls. Flush final traces with water. Keep spills and cleaning run-off materials out of municipal sewers or open bodies of water.
MFG. BY: SAFE ENCASUREMENT SYSTEMS EMERGENCY CONTACT: (800) 424-9300 ADDRESS: 7860 Dana Point Court Las Vegas, NV 89117-1927 Revised: February 2002 Info. Phone: (888) 277-8834			
SECTION I - MANUFACTURER ID.		SECTION V - REACTIVE DATA	
PRODUCT NUMBER: SE-170-MR (formerly SE-170) PRODUCT NAME: High Gloss Surface Coating for Encasement Surfaces PRODUCT CLASS: Specialty Acrylic Coating.		STABILITY: Stable. CONDITIONS TO AVOID: <i>Keep from freezing.</i> INCOMPATIBILITY (MATERIALS TO AVOID): None reasonably foreseeable. HAZARDOUS POLYMERIZATION: Will not occur HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Will not occur.	
SECTION II - HAZARDOUS INGREDIENTS		SECTION VI - HEALTH HAZARD DATA	
This product contains no heavy metals or fibers. This product contains a mold inhibiting additive.		EFFECTS OF OVEREXPOSURE: INHALATION: VAPORS - mist can cause headache, nausea and irritation of the nose, throat and lungs. EYE CONTACT: Slightly irritating to eyes. SKIN EXPOSURE: Irritating to skin upon prolonged or repeated contact.	
SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS		SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE.	
APPEARANCE: White liquid BOILING POINT: 100°C (212°F) Specific Gravity: 1.2 (water = 1.0) VAPOR DENSITY: less than 1.0 VAPOR PRESSURE: (mm Hg @ 20°C) = 18 PRODUCT WEIGHT: 10.0 lb. per US gallon EVAPORATIVE RATE: equal to water V.O.C. = 0.8 lb. per US Gallon PERCENT VOLATILE (by volume): 66%		EMERGENCY AND FIRST AID PROCEDURES: For inhalation, move subject to fresh air. For eye contact, flush with large amounts of water for at least 15 minutes. See a physician if irritation persists. Wash effected skin area with soap and water. If swallowed, dilute by giving 2 glasses of water to drink and CALL A PHYSICIAN IMMEDIATELY. Never give anything by mouth to an unconscious subject.	
SECTION IV - FIRE & EXPLOSION HAZARD DATA		OTHER PRECAUTIONS: DO NOT TAKE INTERNALLY. <i>KEEP AWAY FROM CHILDREN.</i>	
FLAMMABILITY CLASSIFICATION: DOT - NOT REGULATED FLASH POINT – Non-combustible LEL - N/A EXTINGUISHING MEDIA: N/A UNUSUAL FIRE & EXPLOSION HAZARDS: Material can splatter above 212°F Polymer film can burn.		STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Keep Spectators away. WEAR SKIN, EYE, AND RESPIRATORY PROTECTION DURING CLEANUP. Dike and contain with inert absorbent materials (sand, earth, etc.). Transfer to containers for recovery or disposal.	
SE-170-MR-msds 02-2002		SECTION VIII - CONTROL MEASURES.	
		VENTILATION: GENERAL VENTILATION IS RECOMMENDED DURING NORMAL USE. LOCAL VENTILATION MAY BE REQUIRED DURING CERTAIN OPERATIONS TO PREVENT INHALATION OF VAPORS.	
		RESPIRATORY PROTECTION: Wear respirator MSHA or NIOSH APPROVED (or the equivalent) ORGANIC VAPOR/PARTICULATE RESPIRATOR. IN CASE OF POOR VENTILATION (or exposure to spray mist), USE NIOSH APPROVED ORGANIC VAPOR MASK.	
		PROTECTIVE GLOVES: IMPERVIOUS GLOVES FOR PROLONGED OR REPEATED CONTACT.	
		EYE PROTECTION: CHEMICAL SPLASH GOGGLES (ANSI 2-87.1) or EQUIVALENT.	
		OTHER PROTECTIVE EQUIPMENT AND MEASURES: UNHINDERED ACCESS TO SAFETY SHOWER AND EYE WASH STATIONS. AS A GENERAL HYGIENIC PRACTICE, WASH HANDS AND FACE AFTER USE. SHOWERS AND CLEANING OF CLOTHES ARE RECOMMENDED.	
		SECTION IX - REGULATORY INFO.	
		DOT PROPER SHIPPING NAME: Not Regulated. Follow all applicable OSHA and EPA regulations concerning normal latex spraying activities.	