

HazMat Abatement by Encasement Manage in Place Asbestos, Lead-based Paint, Mold & Mildew

BY FRED BUDDE AND BOB MOISON, PE

Hazardous materials that are found in and on buildings such as asbestos, lead-based paint (LBP) and mold and mildew are a problem only when they become airborne and are capable of being inhaled or ingested. The principal method for dealing with them has been removal and replacement, but management-in-place remediation is getting more and more attention.

Due to the high cost and dangers of removal and replacement of contaminated surfaces, OSHA, the EPA and HUD are promoting, where possible, non-disruptive management-in-place remediation techniques.

One satisfactory method of management-in-place has been to use encapsulants. However, encasement now



It's easy to match the cart with the work!



Poly Box Trucks in 14 sizes and two container styles make it easy to match the cart to the application. Containers are molded of high-impact polyethylene for long service. The heavy-duty line is reinforced with four vertical ribs for super rigidity and strength. Rounded corners on the sides and bottom make cleaning simple and easy.

Available in gray, red or blue. Molded of USDA/FDA approved materials upon request.

To locate closest distributor: Call 1-800-533-2475 or email us at sales@amerikart.com



www.amerikart.com

© 2003 Ameri-Kart/Myers Industries 973121



THE MOST NOTORIOUS WORKPLACE KILLER DOESN'T CARRY A GUN.



According to the National Safety Council, the #1 killer in the workplace is slips and falls. In fact, slips and falls kill more workers than fire, chemicals and electrocution combined. If you've ever had to tell a co-worker's family that someone they love was hurt, you know how real the problem is. That's why OSHA and ADA surface treatment guidelines have been toughened, tightened and written into law. And that's why you can count on serious legal problems and heavy expenses if you don't comply.

The solution to this problem? American Safety Technologies Anti-Slip Coatings. Just roll them on and you have a heavily textured anti-slip surface that exceeds OSHA and ADA regulations. In fact, it will stay slip-resistant even when contaminated by oil or chemicals.

Call us today and we'll send you all the information it takes to stop this killer in its tracks.



Anti-Slip Coatings 1-800-631-7841
www.asanti-slip.com

© 2004 ITW/American Safety Technologies

CIRCLE 23 ON READER SERVICE CARD

CIRCLE 22 ON READER SERVICE CARD

represents an advanced method of management-in-place that goes beyond encapsulation in that the surface hazard is first stabilized before it is encapsulated.

Encasement offers less disruption and permits dust-free surface stabilization, reducing the concern of hazardous materials being released after encasement if the abated surface is compromised in any way.

Contrary to common perceptions, both encapsulation and encasement are EPA-approved forms of abatement. Encapsulation and encasement are used for M&M remediation to prevent the re-growth of M&M out of porous surfaces that have been cleaned and disinfected and to prevent the growth on newly coated surfaces of fresh M&M.

Encasement has been used to abate ACM fireproofing and thermal insulation along with surfaces coated with asbestos-containing paint and textured ceilings containing asbestos. Some other surfaces abated via encasement include ACM based grouts and mortars. LBP has also been abated via encasement coatings on homes (both inside and outside), in industrial facilities, schools and universities, and commercial and government buildings. More recently, encasement has been used increasingly to deal with mold and mildew in buildings on walls, ceilings and structural members as well as in HVAC systems (on drain pans and over insulated and uninsulated surfaces).

The versatility of encasement is illustrated by one project in which encasement was used on ACM, LBP, and M&M in the same basement!

The Traditional Approach – Removal and Replacement

The removal of ACM followed by replacement with alternative insulating materials or fireproofing and the removal of LBP followed by repainting are procedures that suffer from many disadvantages. Even situations involving non-hazardous surfaces such as fiberglass insulation, etc. contaminated with M&M present significant safety issues.

Extensive precautions are required to protect workers and prevent the release of the hazardous materials into the environment. This work is highly regulated by governmental authorities on a federal, state and local basis. In spite of the best efforts by trained and licensed abatement contractors, accidents can still occur in which hazardous materials are released into the environment. As an indication

of the difficulty in completing an ACM removal project, in nearly all situations it is necessary to spray a “lock down” coating on all cleaned surfaces before the final clearance can be achieved.

So even with abatement by removal and replacement, some remaining ACM is encapsulated.

1. **Cost** - The cost of abatement in this manner is high. Typical costs are in the range of \$5-10 per square foot or more for LBP and \$5-20 per square foot or more for ACM.

2. **Time** – The extensive amount of time required for removal and replacement frequently leads to high relocation costs. This added expense is rarely factored in, and is frequently of the same magnitude as the cost of abatement.

2. **Hazardous Waste** – The waste generated must be disposed of in accordance with prevailing regulations (usually in an approved hazardous waste landfill) and the owner retains the liability for safe disposal and permanent storage indefinitely. *(Continued on page 30)*

Code Compliance is Different than ADA Accessibility.....

- ADA Legislation Mandates access

- Building Codes Mandate access compliant to Specific Guidelines

.....How do Your Facilities Measure UP?

.....Are You Taking Unnecessary RISK?



If ADA Access & Code Compliance are your Responsibility, We Can Help:

- compliance management
- risk assessment / ADA & NFPA compliance
- fiscal responsibility
- ADA requirements (self-evaluation, timely transition plan)
- evaluation of existing modular access/egress products
- optional surface heat trace available for ice & snow

“Rapid Ramp” is.....

- Adjustable
- Portable
- Durable
- Code Compliant
- ADA, NFPA, ANSI, DSA, UBBC, BOCA Florida SREF & more
- Cost Effective
- Maintenance Free
- Low Installation & Removal Cost
- Next Day Delivery & Set-up

NEW PRODUCT!!!

We offer a Variety of Lease/purchase and Maintenance Options

Call Today for more Information.

(800) 543-1835



CIRCLE 48 ON READER SERVICE CARD

When encasing LBP, very little or no surface preparation is required in most cases.

Management-In-Place Methods

The EPA presently accepts three methods of management-in-place.

1. **Enclosures** – Dust-tight barriers such as sheetrock or plywood are erected to protect against the release of the hazardous material into the environment. When the enclosure is eventually removed, the hazardous material is once again exposed and it usually has become more friable and prone to being released into the atmosphere. Care must be taken to insure that untrained or uninformed workers do not re-expose the hazardous surfaces unknowingly and endanger themselves and/or the inhabitants by causing a release into the environment.

2. **Encapsulation** – A coating material that passes EPA-specified ASTM tests is applied over a surface to prevent the release of hazardous materials into the atmosphere. A problem experienced with encapsulants in some cases is that the added weight of the encapsulant can cause ACM fire-proofing on ceilings or walls to delaminate. A second potential problem with encapsulants is that if the coating is compromised (e.g. by a forklift truck running into a column that has been encapsulated) the potential for release of the hazardous material into the environment is once again present. With LBP a significant amount of scraping of loose, flaking paint is often required to provide a stable surface before the encapsulant that is applied can be expected to achieve adequate adhesion.

3. **Encasement** – A 2-coat system, which also passes EPA-specified ASTM testing, wherein the first coat (primer) stabilizes the substrate by penetrating into the friable ACM and through the loose, flaking paint, and cures into a flexible film that mitigates these hazardous properties. The second coat bonds to the topcoat providing a tough, longlasting, monolithic, composite coating system that prevents the release of any hazardous material into the environment. Because of the penetration of the primer, the adhesion of the overall system is increased, a necessity as the weight of

the system increases.

Additionally if the outer coat is compromised in any manner, there is little or no risk of the hazardous material being released because the surface-stabilizing primer has mitigated the brittle, chalky and friable properties of the hazardous surface. In a very real sense, encasement can be viewed as “stabilization + encapsulation.”

Encasement

The coating materials that make up the basic encasement system are water-based acrylic elastomers that contain no volatile organic compounds (VOC's). As such, they are very safe to work with. A corrosion-inhibiting version of the primer is used when dealing with metal surfaces.

Spraying, brushing or rolling may be used to apply all of the products and cleanup is with water.


Use of a coatings technology-based solution such as encasement usually results in savings of 50-80 percent when compared with the cost of removal and replacement, not including comparable savings in relocation costs in many cases. According to the EPA, to qualify as an approved 20-year encapsulant/encasement system for use over LBP the coatings must pass a series of ASTM performance tests that are encompassed by ASTM E1795-97. Little or no hazardous waste is generated.

Because this is elastomeric technology, cracking, chipping or peeling will never occur. When encasing most forms of ACM, spraying is recommended to prevent disturbing the surface.

Once the primer has been applied, the surface is stable and there is no longer any risk of asbestos getting into the environment. In fact, tests have shown that there is minimal release of asbestos during the spraying of the primer, so the abatement of ACM by encasement is much safer from the standpoint of worker safety.

When encasing LBP, very little or no surface preparation is required in most cases. In general, only very loose, flaking paint need be removed, which should be done in a dust-free manner.


When dealing with masonry surfaces, it is usually necessary to remove any efflorescence, which is best done by power washing, which also serves to remove any



**Join
Team
Clean!**

LSS
LAB SAFETY SUPPLY

is your total
**cleaning
solution**



Get a **Free** 365-page
Janitorial Catalog today!

1-800-356-0783 - www.LSS.com

CIRCLE 39 ON READER SERVICE CARD

loose, flaking paint. When dealing with metal surfaces, power washing is also recommended, and it is further recommended that a soluble salt remover be added to the wash water to facilitate the removal of soluble salts that cause corrosion.

Mold & Mildew

When dealing with M&M, the surface is first cleaned and disinfected. Then, to prevent the regrowth of the M&M, particularly on any porous surfaces that will remain, the surface is coated with the encasement primer to achieve a stable surface, which is over-coated with the appropriate topcoat.

Any coatings used in the remediation of M&M should pass ASTM D3273/D3274, which indicates that the coating will not support the growth of M&M. Most coatings that pass this testing have accomplished this by adding a poison to the coating, an EPA-registered pesticide.

An important advantage of the encasement coating system we prefer is that it passes this testing as is, i.e. without the addition of a poison. The importance of this fact becomes clearer when one considers the instances of people who, upon re-inhabiting their property after the M&M remediation is complete and an encapsulant with a poison has been applied, then begin to develop allergic reactions to the coating's mildewcide..

One particular encapsulant used for M&M remediation includes an iodine-containing mildewcide that is known to produce allergic reactions among a significant portion of the populace. Another encapsulant used for this purpose employs a chlorine-containing mildewcide, also known to cause sensitivity issues.

The basic encasement system will provide adequate protection against the future growth of M&M in most cases without the use of a mildewcide. In extreme cases, a few mils of a high-gloss topcoat can be applied over the encasement system to provide added protection against the future growth of M&M. This added protection comes from the gloss and its nature to soil less, -and the improved ability to clean it. As a final option, a high-gloss coating can be used that contains an EPA-approved mildewcide that contains neither iodine nor chlorine. □

Fred Budde is marketing director of Safe Encasement Systems – Midwest of Eagan, MN and Bob Moison, PE, is technical director of the firm. They can be reached at febudde@juno.com or (651) 454-4107.

FIND AND EVALUATE EXCESS MOISTURE AND HUMIDITY FAST AND ACCURATELY WITH TRAMEX NON-DESTRUCTIVE MOISTURE METERS.

Excess Moisture and humidity can damage the fabric of buildings and lead to microbial growth that can seriously affect the residential health of a building.

TRAMEX Moisture Detection Equipment for Facility Maintenance Professionals.



- **Non-Destructive moisture meters** to locate and measure hidden moisture and trace leaks in building materials, walls, floors, ceilings, roofs and equipment.

- **Digital Hygrometers** to evaluate relative humidity, temperature and dew point in the building environment and materials.

- **Special all in one building inspection kits for:** the moisture and humidity monitoring needs of the Facility Maintenance Professional.



For Information: **TRAMEX** c/o Black Hawk Sales.
28 Pin Oak Drive Littleton, CO 80127.

Tel: 303 972 7926. Fax: 303 972 7106. Web: www.tramexltd.com
Email: dennisw@tramexltd.com

CIRCLE 43 ON READER SERVICE CARD



Safe, Effective and Affordable

Solutions for Hazardous and Difficult Surfaces including:

Mold Asbestos
Lead-Paint Corrosion

Better SAFE than Sorry...

Phone (888) 277-8834

www.safeencasement.com

75 Year Corrosion Protection Systems

Call (877) METALIZ

CIRCLE 42 ON READER SERVICE CARD